

EMU32.x1M - Single Tariff

EMU32.x2m - Double Tariff

7-digit mechanical display

EMU32.x1M:

Including one decimal position
000000.0 kWh, figure size 5 x 3 mm

EMU32.x2m

Includes one decimal position
000000.0 kWh, figure size 1.2x4 mm

Technical data:

- Direct connection up to 63A
- Nominal voltage Un: 3 x 230/400 VAC +/- 20%
3 x 127/220 VAC +/- 20%
3 x 63 / 110 VAC +/- 20%
- Nominal (Maximum) Current: 5 (63)A
- Measuring range: 0.025 bis 63A
- Starting current <25mA
- Operating net frequency: 45 - 65Hz: 45 - 65Hz
- Meter burden: <0.8 W / Phase
- Accuracy class 2 according EN 62053-21
- Operating Temperature range: - 10°C bis +50°C
- Storage Temperature: -40° C to +70° C
- Tariff control: 230VAC,
Tariff 2 aktive = Voltage applied
- Weight: 320g
- In conformity with CE and IEC1036
- Installation: DIN BAR 35mm according EN60715
- S0 Impulse output: 10 Imp. / kWh, Ti = 120ms
- Approvals: PTB (Germany) and METAS (Switzerland)
- Current and voltage circuits galvanically separated.

